

HEALTHIER CHOICE®

100% HIGH DENSITY MEMORY FOAM CARPET CUSHION

DESCRIPTION

Premium 100% high density memory foam cushion for use under all carpet styles.

STYLE / SKU / ROLL SPECS

WHT180 – 6' x 30' roll, 180 sq. ft., 20 sq. yd. (75.5 lbs.)

WHT270 – 6' x 45' roll, 270 sq. ft., 30 sq. yd. (110 lbs.)

MATERIAL

Frothed polyurethane – a visco-elastic “memory foam” material.

THICKNESS

0.5" (1/2")

DENSITY

10lbs/ft³ (48.82kg/m³)

SOUND RATING

Impact Insulation Class (ASTM E492-90) 90 IIC

WATER RESISTANCE

British Spill Test Method E Pass

Breathable Integral Skin Barrier, allows vapor to pass while blocking liquid spills, making clean-up easier and more effective.

INSULATION RATING

R-Factor (ASTM C518-10) 1.60

Excellent for radiant heated floors.

FIRE RATING

NBS Smoke Chamber <100 max

Pill Test (FF 1-70) Pass

DURABILITY

Compression Set 7% max

Indentation Load Deflection (25%) 4.20 lbs/ft²

Indentation Load Deflection (65%) 20.00 lbs/ft²

INSTALLATION

Engineered for stretch-in installation. Install foam side up.

WARRANTY

Warranted for a lifetime to the original purchaser.

RENEWABLE CONTENT

IMade in part with eco-friendly soybean oil, lessening dependence on petrochemicals. This reduces global warming emissions and the need for foreign oil while supporting local farmers and local producers.

Applicable towards LEED Credit MR 6 – Rapidly Renewable Resources.

INDOOR AIR QUALITY

CRI Green Label certified. The only carpet cushion GREENGUARD Indoor Air Quality Certified® as a low emitting interior building material.

Applicable towards LEED Credit EQ 4.3 – Low Emitting Product.

ANTIMICROBIAL

Ultra-Fresh® Antimicrobial prevents mold, mildew, and bacterial growth while controlling dust mites for life-long odor free installation.

RECYCLABLE


Zero-Landfill Manufacturing waste, all materials are reused in products with recycled content. Post consumer recyclable, a valued commodity as recycled foam in the manufacturing of rebond padding.

NOTE: Specification values subject to a 7% manufacturing tolerance.

HC WHITE




6' X 30'
ROLL



14"
ROLL
DIAMETER



6' X 45'
ROLL



18.5"
ROLL
DIAMETER
CORE SIZE: 3.625"

